

**MATERIAL SAFETY DATA SHEET**

Page 1

Revised edition No 1

Date : 28 / 01 / 2015

Supersedes : 0 / 0 / 0

JAX OLEUM**1. IDENTIFICATION OF THE SUBSTANCE / PREPERATION AND THE COMPANY/ UNDERTAKING**

Identification of the product : Jax Oleum.
Type of product : Natural oil for wood.
Use : Professional use. DIY. See instructions on product for detailed information.
Emergency phone no. : + 271 14447221.

2. HAZARDS INDENTIFICATION

Risk Phrases : None.
Primary route of exposure : Inhalation.
Symptoms relating to use : Seek medical attention if any ill effects develop.
- Inhalation : Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
- Skin contact : May cause sensitivity on skin with contact.
Repeated or prolonged skin contact may cause irritation.
- Eye contact : Contact with the eyes is likely to cause irritation.
- Ingestion : Abdominal pain, nausea.
Note : This product is not considered to be hazardous but contains hazardous products (Directive 1999/45/EC).

3. COMPOSITION / INFORMATION ON INGREDIENTS

This product is not considered to be hazardous but contains hazardous products (Directive 1999/45/EC)

Substance Name	Contents	Cas No	EC no	Index No	Classification
Oleum terebinthinae	<10%	8006-64-2	-	-	Xn; R65 R66

4. FIRST AID MEASURES

First Aid Measures
- Inhalation : Assure fresh air breathing.
- Skin contact : Wash skin with mild soap and water.
- Eye contact : Rinse immediately with plenty of water. Seek medical attention if irritation continues
- Ingestion : DO NOT INDUCE VOMITING. Seek Medical advice (show label where possible).

5. FIRE- FIGHTING MEASURES

Prevention
Extinguishing media : Dry chemical. Foam. Carbon dioxide.
Specific hazards : Incomplete combustion will generate poisonous carbon monoxide, carbon dioxide and other toxic gases.
Protection against fire : Use water spray or fog for cooling exposed containers. Do not enter fire area without proper protective equipment, including respiratory protection.
Special procedures : Avoid firefighting water to enter environment.

**MATERIAL SAFETY DATA SHEET**

Page 2

Revised edition No 1

Date : 28 / 01 / 2015

Supersedes : 0 / 0 / 0

JAX OLEUM**6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions** : Equip cleanup crew with proper protection.
- Environmental precautions** : Prevent entry to sewer and public waters. Notify authorities if product enters sewers or public waters.
- Clean up methods** : Clean up any spills as soon as possible, using an absorbent material to collect it. Use suitable disposal containers.

7. HANDLING AND STORAGE

- Precautions in handling and storage** : Provide local exhaust or general room ventilation.
- Storage** : Store in tightly closed, properly ventilated containers away from heat, sparks open flame.
Protect from freezing.
- Handling** : Handle in accordance with good industrial hygiene and safety procedures, Wash hands and other exposed areas with mild soap and water before eating, drinking , smoking etc.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION


- Personal protection**
- **Respiratory protection** : No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation.
 - **Hand protection** : In case of repeated or prolonged contact wear gloves.
 - **Eye protection** : Eye protection should only be necessary where liquid could be splashed or sprayed.
 - **Ingestion** : When using, do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state at 20° C** : Liquid
- Odour** : Natural Oil
- Boiling point (° C)** : 185 °C
- Density (kg/m3)** : 0,90 - 0,95
- Vapour pressure (20°C)** : 0,05 kPa
- Flash point (°C)** : 66 °C
- Volatile organic compounds :** : 98 g/l

10. STABILITY AND REACTIVITY

- Hazardous decomposition products** : Stable under recommended storage and handling conditions (see section7).
When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen ect..
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

	MATERIAL SAFETY DATA SHEET	Page 3
		Revised edition No 1
		Date : 28 / 01 / 2015
		Supersedes : 0 / 0 / 0
JAX OLEUM		

11. TOXICOLOGICAL INFORMATION

Toxicity information : This product is not considered to be hazardous but contains hazardous products (Directive 1999/45/EC).

12. ECOLOGICAL INFORMATION

Ecological effects information : There is no data available on the preparation itself.
The product should not be allowed to enter drains or water courses.

13. DISPOSAL CONSIDERATIONS

General : Avoid release to the environment.
Dispose in a safe manner in accordance with local/national regulations.
Dispose of this material and container at hazardous or special waste collection point.

14. TRANSPORTATION INFORMATION

ADR/RID : Not applicable.
- IMO-IMDG code : Not applicable.
- ICAO/IATA : Not applicable.

15. REGULATORY INFORMATION

Symbol (s) : None.
R Phrase (s) : None.
S Phrase (s) : S2 : Keep out of the reach of children.

16. OTHER INFORMATION

Further Information : Specifications and technical information on product may be obtained from your supplier.

R-phrases not concerned by the classification of the product : R65 : Harmful ; may cause lung damage if swallowed
R66 : Repeated exposure may cause skin dryness or cracking

DISCLAIMER OF LIABILITY The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without warranty, expressed or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expenses arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.
