

TECHNICAL DATA SHEET



PRODUCT DETAILS

Product Name:	2K Matt Sealer
Product Description:	Milky liquid that is the base and clear liquid that is the hardener, clear when dry.
Areas of Application:	Timber/Wooden surfaces from furniture to floors. Ideal for high traffic areas
Substrate Material:	For extra protection and water resistance on oiled floors and surfaces

SURFACE PREPARATION

Surface Preparation:	Clean and dry
Substrate Sanding Grits:	120 grit
Comments on Sanding:	Remove dust created from sanding before applying

APPLICATION

Airless:	N/A
Airless low pressure:	N/A
Airmix:	N/A
Compressed air spaying:	Low pressure spray gun
Wiping sponge roller:	Mohair roller
Non-wiping sponge roller:	Sponge roller
Expel with brush/paintbrush:	N/A
Smooth Roller:	Sponge/Foam roller
Spreading:	10m ² per liter when applying 2 coats. 20m ² per liter when applying 1 coat.

TECHNICAL DATA

Yield per coat:	20m ² per litre per coat
Flow time (+/- 15%):	N/A
Proportion of renewable raw material:	0
Non-volatile proportion:	0,9
Conditions of transport:	Under 140 °C
VOC:	A
Shelf life:	1 year. Pot life once mixed 8 hours
Number of coats (max):	2 (two) coats. 3 (three) coats is recommend for high traffic areas.
Amount per layer (minimum):	5 ml/m ²
Amount per layer (max):	15ml/m ²
Total application volume:	1 l - 10m ²
Drying:	Full cure takes 36 hours, light traffic after 8 hours.
Finishing:	Will appear clear once dry.
Sealing:	Once applied to timber, creates water resistance barrier

PROCESSING & SPECIAL NOTES

Processing Instructions:	Apply an ever coat onto a freshly sanded and clean surface. Allow to dry, lightly buff the surface, remove any dust from sanding and apply second coat.
Particular Instructions:	Apply to clean, dry surface

GENERAL WORKMANSHIP NOTES

General Instruction on Workmanship:	ready to be sealed. Apply onto dry, dust free surface using short mohair roller or cloth. Leave to dry for a few hours. Lightly sand and
-------------------------------------	--

Our technical information is continually adapted to keep up to date with the latest technology and statutory regulations. The indicated values are no specification, but typical product data. The latest version is always available online at www.jaxoleum.co.za or talk to your local account manager. This information is for advice and is based on the best knowledge available and careful research in line with the current state of the art. This information cannot be held as legally binding. We also refer you to our terms and conditions of business. Material safety data sheet is provided in accordance with EC regulation no. 1907/2006.