

TECHNICAL DATA SHEET



PRODUCT DETAILS

Product Name:	Q8 Silk/Gloss/Matt Sealer
Product Description:	Milky liquid that dries clear
Areas of Application:	Wooden furniture, any wooden item that requires sealing
Substrate Material:	For extra protection from daily wear and tear. To apply a water resistant layer to an oiled/stained surface

SURFACE PREPARATION

Surface Preparation:	Clean and dry
Substrate Sanding Grits:	120 grit
Comments on Sanding:	Wipe off all sanding dust before applying the sealer

APPLICATION

Airless:	N/A
Airless low pressure:	N/A
Airmix:	N/A
Compressed air spaying:	N/A
Wiping sponge roller:	Mohair roller
Non-wiping sponge roller:	Sponge roller
Expel with brush/paintbrush:	N/A
Smooth Roller:	Sponge/Foam roller
Spreading:	10m ² per liter when applying 2 coats. 20m ² per liter when applying 1 coat.

TECHNICAL DATA

Yield per coat:	15m ² per litre per coat
Flow time (+/- 15%):	N/A
Proportion of renewable raw material:	0
Non-volatile proportion:	0
Conditions of transport:	Under 140 °C
VOC:	A
Shelf life:	1 (one) year
Number of coats (max):	2 (two) coats
Amount per layer (minimum):	5 ml/m ²
Amount per layer (max):	15ml/m ²
Total application volume:	1 l - 10-20m ²
Drying:	Full cure takes 36 hours, light traffic after 6 hours
Finishing:	Will appear clear once dry with finish based on chosen product - either silk, gloss or matt
Sealing:	Once applied to timber, create water resistance barrier

PROCESSING & SPECIAL NOTES

Processing Instructions:	Apply an even coat onto a freshly sanded and clean surface. Allow to dry, lightly buff the surface, remove any dust from sanding and apply second coat.
Particular Instructions:	Apply to clean, dry surface

GENERAL WORKMANSHIP NOTES

General Instruction on Workmanship:	Apply an even coat to a freshly sanded clean surface. Allow to dry. Lightly buff and remove dust before applying second coat.
-------------------------------------	---

Our technical information is continually adapted to keep up to date with the latest technology and statutory regulations. The indicated values are no specification, but typical product data. The latest version is always available online at www.jaxoleum.co.za or talk to your local account manager. This information is for advice and is based on the best knowledge available and careful research in line with the current state of the art. This information cannot be held as legally binding. We also refer you to our terms and conditions of business. Material safety data sheet is provided in accordance with EC regulation no. 1907/2006.